

DieselTest

Информация о насосе

Part number: 0445010145
Test type: CR/CP3S3/L90/20-8911S
Steps: 9
Swap pressuare, kPa: 370
Reverse pressuare, kPa: 20

Информация о клиенте

Результат

Clean run

Supply 12V; Rotation L; Pressuare 0 MPa; Speed 500 RPM;

Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;

No Flow 1

No Flow 2

HP 0

Warm up

Supply 12V; Rotation L; Pressuare 25 MPa; Speed 2000 RPM;

Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;

Flow 1 104 (X)

Flow 2 258.7 (X)

HP 248

Air elimination

Supply 12V; Rotation L; Pressuare 0 MPa; Speed 3500 RPM;

Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;

No Flow 1

No Flow 2

HP 0

Visual check	Supply 12V; Rotation L; Pressuare 30 MPa; Speed 2500 RPM; Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;	Flow 1 95.88 (X) Flow 2 698.5 (X) HP 292
kenn . 1	Supply 12V; Rotation L; Pressuare 50 MPa; Speed 3500 RPM; Flow 1 Max 181.8; Flow 1 Min 128.6; Flow 2 Max 76; Flow 2 Min 44;	Flow 1 122.6 (X) Flow 2 157.6 (X) HP 500
Fill out	Supply 12V; Rotation L; Pressuare 0 MPa; Speed 3500 RPM; Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;	Flow 1 15.96 (X) Flow 2 439.6 (X) HP 81
Zero delivery	Supply 12V; Rotation L; Pressuare 0 MPa; Speed 3500 RPM; Flow 1 Max 2; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;	No Flow 1 Flow 2 34.56 (X) HP 8
efficiency	Supply 12V; Rotation L; Pressuare 160 MPa; Speed 1000 RPM; Flow 1 Max 51.9; Flow 1 Min 35.1; Flow 2 Max 0; Flow 2 Min 0;	Flow 1 46.02 (OK) Flow 2 121.7 (X) HP 1599
start	Supply 12V; Rotation L; Pressuare 20 MPa; Speed 180 RPM; Flow 1 Max 9.3; Flow 1 Min 7.7; Flow 2 Max 64; Flow 2 Min 34;	Flow 1 12.66 (X) Flow 2 360.9 (X) HP 199

