

# DieselTest

## Информация о насосе

Part number: 0445010145  
Test type: CR/CP3S3/L90/20-8911S  
Steps: 9  
Swap pressuare, kPa: 370  
Reverse pressuare, kPa: 20

## Информация о клиенте

## Результат

---

### Clean run

Supply 12V; Rotation L; Pressuare 0 MPa; Speed 500 RPM;  
Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;

No Flow 1  
No Flow 2  
HP 0

### Warm up

Supply 12V; Rotation L; Pressuare 25 MPa; Speed 2000 RPM;  
Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;

Flow 1 104 (X)  
Flow 2 258.7 (X)  
HP 248

### Air elimination

Supply 12V; Rotation L; Pressuare 0 MPa; Speed 3500 RPM;  
Flow 1 Max 0; Flow 1 Min 0; Flow 2 Max 0; Flow 2 Min 0;

No Flow 1  
No Flow 2  
HP 0

Visual check	Supply 12V;    Rotation L;    Pressuare 30 MPa;    Speed 2500 RPM;  Flow 1 Max 0;    Flow 1 Min 0;    Flow 2 Max 0;    Flow 2 Min 0;	Flow 1 95.88 (X)  Flow 2 698.5 (X)  HP 292
kenn . 1	Supply 12V;    Rotation L;    Pressuare 50 MPa;    Speed 3500 RPM;  Flow 1 Max 181.8;    Flow 1 Min 128.6;    Flow 2 Max 76;    Flow 2 Min 44;	Flow 1 122.6 (X)  Flow 2 157.6 (X)  HP 500
Fill out	Supply 12V;    Rotation L;    Pressuare 0 MPa;    Speed 3500 RPM;  Flow 1 Max 0;    Flow 1 Min 0;    Flow 2 Max 0;    Flow 2 Min 0;	Flow 1 15.96 (X)  Flow 2 439.6 (X)  HP 81
Zero delivery	Supply 12V;    Rotation L;    Pressuare 0 MPa;    Speed 3500 RPM;  Flow 1 Max 2;    Flow 1 Min 0;    Flow 2 Max 0;    Flow 2 Min 0;	No Flow 1  Flow 2 34.56 (X)  HP 8
efficiency	Supply 12V;    Rotation L;    Pressuare 160 MPa;    Speed 1000 RPM;  Flow 1 Max 51.9;    Flow 1 Min 35.1;    Flow 2 Max 0;    Flow 2 Min 0;	Flow 1 46.02 (OK)  Flow 2 121.7 (X)  HP 1599
start	Supply 12V;    Rotation L;    Pressuare 20 MPa;    Speed 180 RPM;  Flow 1 Max 9.3;    Flow 1 Min 7.7;    Flow 2 Max 64;    Flow 2 Min 34;	Flow 1 12.66 (X)  Flow 2 360.9 (X)  HP 199

